


T5, T8 LAMP



### SPECIFICATIONS

- HOUSING** Two piece snap together top/bottom extruded aluminum housing up to 12' long
- FINISH** Satin anodized or white paint finish standard. Custom finish optional
- LENS** Extruded, snap-on clear or opal white linear prismatic serrated widespread lens
- BALLAST** Integral 120 or 277V electronic ballast. Dimming ballasts available.

### LAMPS - FIXTURE LENGTHS

**T5 LAMP INFORMATION & FIXTURE LENGTHS**

WATTS	LAMP DIM	SINGLE	TANDEM
14, 24W HO	22.17"	25"	N/A
21, 39W HO	33.89"	37"	71"
28, 54W HO	45.80"	49"	95"
35, 80W HO	57.61"	61"	119"

**T8 LAMP INFORMATION & FIXTURE LENGTHS**

WATTS	LAMP DIM	SINGLE	TANDEM
17W	24"	26"	N/A
25W	36"	38"	74"
32W	48"	50"	98"
40W	60"	62"	122"

### PART NO.

SERIES	WATTS	LENS	VOLTS	FEED	FINISH	LENGTH
ALX2-RLR-WL-T5	REFER	C – CLEAR	120	EF – END FEED	S – SATIN	SPECIFY
ALX2-RLR-WL-T5T	TO	W – WHITE	277	BF – BACK FEED	W – WHITE	
ALX2-RLR-WL-T8	CHART		D-DIM.	RF – ROW FEED		
ALX2-RLR-WL-T8T	ABOVE					



2001431 ("T") Denotes TANDEM Lamp. Consult factory for row mounting.